

PRINTERS & PEOPLE YOU CAN TRUST

3200, 3200 TURBO, 5000 ROLL TO ROLL PRINTERS







SUPERIOR PRINT PRODUCTION

3200T

5000

ROLL-TO-ROLL PRINTERS

126" MEDIA AREA

126" MEDIA AREA

196" MEDIA AREA

PRINTER HIGHLIGHTS

- > CET Color Roll to Roll printers produce highest speeds and quality at a fraction of the cost offered by competitive models.
- > The K2-Series achieves both quality and speed with the revolutionary Kyocera printhead
- Equipped with robust feed and take up systems.
- Capable of dual roll printing
- > Mesh Kit included

KYOCERA PRINTHEAD

Nozzle quantity: 2656

Pico-liter: Variable 4-6-10pl

Effective Print Width: 112.35 mm

Max Operating Frequency: 50 Khz



SPECIAL FEATURES

TWO ROLLS PRINTING:

Print different image output on 2 rolls of media

WATER COOLED PLATES

For hear sensitive media.


3200 TURO & 5000 RTR ONLY:

AUTO MEDIA WIDTH DETECTION SYSTEM:

Automatically detects the width of media

LINEAR MOTOR & MAGNETIC DRIVE SYSTEM:

High-tech linear motor drive ensures stable carriage movement while the magnetic raster ensures high precision ink drop placement



(1) KYOCERA PRINT HEADS

Featuring variable dots, true grayscale imaging 4, 6, and 10pl

2 WATER-COOLING LED LAMPS

Economical & environmentally-friendly water-cooling LED system

(3) STATIC SUPPRESSION

Dual static suppression kit reduces static on static sensitive media

(4) AUTO MEDIA HEIGHT DETECTION SYSTEM

Detects the height of media

DUAL ROLL FEEDING SYSTEMprint multiple sizes and dual rolls

(6) MESH KIT

Special design to print mesh without linear

(7) WATER-COOLING PRINTING PLATFORM

With adustable suction zone-special design to cool heat-sensitive material

(8) AUTOMATIC NEGATIVE PRESSURE SYSTEM

Negative pressure is automatically controlled through control software

9 ON-BOARD CONTROL MODULE

Independent control module with rich functions that are user friendly

10 MEDIA TENSION ADJUSTMENT CONTROL

Adjust media tension to prevent wrinkling during printing

SPECIFICATIONS

MODEL		3200	3200 TURBO	5000
PRINTHEAD		K2	К2	K2
QUANTITY OF PRINTHEADS		2-4 Single Row	4-10 Symmetric Array	8-10 Symmetric Array
MAX PRINT SPEED	2 pass	1450	2234	2749
	6 pass	895	1680	2067
	9 pass	580	1188	1240
	12 pass	400	784	819
MAX RESOLUTION	1200 X 1200 dpi			
MAX PRINT AREA		126"	126"	196"
MAX MEDIA THICKNESS	2 mm			
MEDIA TYPE	Roll Materials			
INK	Flexible UV Ink			
INK COLOR	CMYK + White (optional)			
MACHINE SIZE (L X W X H)		255" x 52' x 68"	255" x 52" x 68"	350" x 80" x 80"
MACHINE NET Weight		3,969 lbs	3,969 lbs	13,889 lbs
SHIPPING WEIGHT		5,621 lbs	5,621 lbs	18,011 lbs
POWER SUPPLY	220 - 230 VAC. 60Hz 30 AMP (single phase)			
RIP SUPPORT	Onyx			
UV CURING	LED			
ENVIRONMENT	Separated workroom in good cleaning and ventilated condition, avoid direct sunlight Temperature: 64°F - 86°F (18° C – 30° C) Constant Humidity: 45%-70%			





ABOUT CET COLOR





WE GO ABOVE & BEYOND FOR OUR CUSTOMERS

At CET Color, our customers are family and our number one priority. We go the extra mile to ensure that we are available to assist you with all of your printing needs.



EXPERIENCE

We draw on years of experience in the printing industry to create state-of-the-art machines and offer unparalleled service.



WIDE VARIETY OF READILY AVAILABLE PRODUCTS

Our Atlanta facility is stocked with a large inventory of printers, parts, inks and other consumable items that are ready to be shipped.



TRAINING

At CET, we provide unique and meticulous training to both our technicians and your operators because we believe that it is an integral part of owning one of our printers.



OUALITY PRINTERS & PRODUCTS YOU CAN TRUST

CET Color Printers are highly engineered with long life and ease of use in mind. Our team is here to assist you from beginning to end of your printer life.

4450 Commerce Dr. SE

Atlanta, GA 30336







